

Excavations

Subpart P One-hour

Safety

Why the Training?

- People die in excavations!
 - See Fatal Facts
- Regulations
 - 29 CFR 1926,Subpart P



Safety

What We Will Cover




- Regulations
- Competent Person
 - Qualifications
 - Responsibilities
- Hazards of Excavations

Safety

Fycallanca

What We Will Cover



- Soil Classifications
- Protective Systems
 - Sloping
 - Shoring
- Inspections
- Emergency Response

Safety

Regulations

 29 CFR 1926 Subpart P -Excavations BRATIMENT OF LABOR



- Soil evaluations by Competent Person
- Daily Inspections by Competent Person
- Shoring and sloping evaluations by Competent Person
- Stop Work Authority of Competent Person

Safety

STATES OF AN

Competent Person

"Competent person" means one who is capable of identifying existing and predictable hazards in the surroundings or working conditions which are unsanitary, hazardous, or dangerous to employees, and who has authorization to take prompt corrective measures to eliminate them.

Safety

Competent Person

- Qualifications
 - Knowledge of soils and soil classification
 - Understands design and use of protective systems
 - Ability to recognize and test hazardous atmospheres
 - Documented training
 - Prior excavation experience

Safety

Competent Person

- Responsibilities
 - Site safety briefings on excavation safety
 - Daily excavation inspections
 - More frequent if conditions change (e.g. freeze/thaw, rain, vibration)
 - Physically located at the excavation STOP WORK AUTHORITY!!!

Safety

Excavation Hazards

- Surface encumbrances
- Utilities
- Access/Egress
- Vehicle traffic
- Falling loads
- Mobile equipment

- Hazardous atmospheres
- Water accumulation
- Adjacent structures
- Loose rock or soil
- Falls
- Cave-in

Safety

Surface Encumbrances

 Need to be removed or supported

e.g. fencing structure, materials

Safety

Utilities

- Underground
 - Locate prior to digging
 - Certify deactivation
 - Protect, support, or rem










Safety

Utilities

- Aboveground
 - De-energize or
 - Isolation from power lines



Safety

Access/Egress

- Note: Poor housekeeping --- # 1 cause of slips, trips and falls on construction projects
 - Debris kept cleared from work areas
 - Mark hazards
 - Barricade or cover holes
- Egress provided-
 - 25' travel distance
 - ladders
 - ramps
 - stairs



Safety

Vehicle Traffic

- Traffic Control
- Traffic Safety

Vests





Safety

Exposure to Falling Loads



- No work under loads
- Operators remain in cab

Safety

Mobile Equipment


- Warning system
 - Barricades
 - Hand signals
 - Mechanical signals
 - Stop logs
 - Grade away from excava



Safety

Hazardous Atmospheres

- Test @ 4' if suspected
 - LEL
 - Oxygen
 - CO
 - H2S
 - Petroleum
 - Other toxics



Safety

Ventilation

- Displace hazardous gases and vapors
- Considerations
 - Heavier than air or lighter than air contaminant
 - Exhausting or blowing in
 - Volume/time required to lower concentrations to acceptable levels



Safety

Excallance

Water Accumulation




- Protection from hazards associated with water accumulation
 - Protection against cave-in
 - Water removal (pumping)
 - Run-off protection
 - Consider temporary shutoff of water lines

Safety

Adjacent Structures

- Ensure structure stabi
 - Shoring
 - Bracing
 - Underpinning
 - Or evaluation by P.E.



Safety

Loose Rock and Soil

- Protection of employees from loose rock or soil
 - Scaling
 - Protective barrier
 - Placing material a least 2' from edge
 - No work on slopes above workers





Safety

Fall Protection

- Any surface 6 feet or more above a lower level shall be protected by:
 - walkways with guardrail systems
 - personal fall arrest sys
- Other options include
 - warning lines systems
 - safety monitoring systems

Safety

Cave-in

- Protection from cave-in requires a systematic approach including:
 - Soil classification
 - Protective systems
 - Inspection
 - Employee training







Safety

Soil Classification


- Soil Classification (Type A,B,or C) determines construction of protective system:
 - Sloping or benching
 - Shoring
 - Timber shoring
 - Aluminum shoring

Safety

Protective Systems

- Required unless:
 - Excavation in stable rock
 - Excavation less than 5 ' (4' some states) and examination by Competent Person determines no potential for cavein







Safety

Protective Systems


- Options Include:
 - Sloping and benching
 - Shoring/sheet piling/ shielding (e.g.trench boxes)
 - Designed by P.E. if deeper than 20'




Safety

Simple Sloping


Type A - 3/4:1



Type B - 1:1



Type C - 1½ :1




Safety

Fycallanca


Benching

Type A



Type B

• (cohesive soil)



Type C

NA

Safety

Shoring

- Based on OSHA Appendices
- Based on Manufacturer data
- Designed by a P.E.



Safety

Timber Shoring Installations




- Appendix C of OSHA regulations
- Requires soil classification
- Based on depth and width of trench
- Consult tables for specs on
 - Cross braces
 - Wales
 - Uprights

Safety


Aluminum Shoring Installations

- Appendix D of OSHA regulations
- Requires soil classification
- Based on depth and width of trench
- Consult tables for specs on
 - Hydraulic cylinders
 - Wales
 - Uprights



Safety

Shields (i.e. Trench Boxes)



Safety

Protective Systems



- Installation
 - Securely connected
 - Employees clear of area under shields during installation
 - Installed to prevent movement
 - Must protect employees while entering excavation

Safety

Protective Systems

- Removal
 - Employees clear of area under shields during removal
 - Shoring removed from the bottom up, SLOWLY!
 - Backfill with removal



Safety

Excavation Inspections

- Daily Inspections of ALL excavations by Competent Person
 - Start of shift, as needed, following rainstorms or other hazard-increasing event
 - Possible cave-ins
 - Protective system failure
 - Water accumulation
 - Hazardous atmospheres
 - Competent person has authority to remove workers from the excavation

Safety



Safety










Evcallanca



- Initial Size-up
 - Type of incident?
 - Cave-in, flooding, medical, fire, spill
 - Injuries?
 - Number and type
 - Missing personnel?
 - Chemical (or sewage) exposures?
 - Safety of excavation for rescuers?

Safety

- Notify:
 - Field personnel
 - HSO = Emergency Coordinator
 - Fire Department
 - Police Department
 - Emergency Medical Services
 (EMS)/Hospital

Safety

- Stabilize cave-in
- Control flooding
- Hazardous Atmospheres?
 - Ventilate
 - SCBA
 - Safety harness and line
 - Basket stretcher





Safety

- The best rescue is the one you never have to make!
 - Practice proper procedures
 - Make sure everything is safe before anybody goes in!

DON'T ROLL THE DICE!!!

Safety